

ULTIMATE



STRONG EUROPE

Together... Stronger!!!



ULTIMATE – Positive plate for CTcP UV

High sensitive plate, developed for optimal use in all CTcP UV platesetters. Fast processing and excellent dot and screen reproduction. It is certified by the main platesetter manufacturers as Lüscher, BasysPrint and Amsky.

- Advantages:
1. High sensitivity.
 2. Wide tolerance in pre-press conditions.
 3. Medium-long run-length.
 4. Excellent screen dot reproduction.



ULTIMATE – Plancha positiva para CTcP UV

Dotada de una alta sensibilidad, está desarrollada para su óptima utilización en equipos de grabación CTcP UV. Rápido procesado y excelente reproducción de punto y tramas. Está certificada por los principales fabricantes de equipos CTcP UV como Lüscher, BasysPrint y Amsky.

- Ventajas:
1. Alta sensibilidad.
 2. Amplia tolerancia en pre-impresión.
 3. Tiradas de media-larga duración.
 4. Excelente reproducción del punto de trama.



ULTIMATE – Plaque positive pour CTcP UV

Dotée d'une sensibilité élevée, cette plaque a été conçue pour une utilisation optimale sur des systèmes de gravure CTcP UV. L'opération est rapide et la reproduction de points et trames excellente. La plaque est d'autre part homologuée par les principaux fabricants d'équipements CTcP UV tels que Lüscher, BasysPrint et Amsky.

- Avantages:
1. Sensibilité élevée.
 2. Grande tolérance en préimpression.
 3. Tirages de moyenne-longue durée.
 4. Excellente reproduction du point de trame.

ULTIMATE TECHNICAL SPECIFICATIONS

TYPE:	CTcP UV Positive plate
PLATE GUAGES:	0,15 / 0,20 / 0,25 / 0,30 / 0,40 mm
COATING COLOR:	Green
LASER CHARACTERISTICS:	Ultra Violet UV at 400 – 410 nm
SENSITIVITY:	50 – 60 mJ/cm ²
SCREEN REPRODUCTION:	1 – 99% at 300 l.p.i.
RESOLUTION:	Up to 3200 d.p.i. and 20 µm FM screening
DEVELOPMENT:	ABCHA-7200 Developer and Replenisher
FINISHING GUM:	ABCH-6970110
APPLICATION:	Sheetfed and web presse
RUN LENGTH (Unbaked):	Up to 100.000 impressions
RUN LENGTH (Baked):	Up to 700.000 impressions
SAFELIGHT:	White: 1 hour / Yellow: 6 hours
SHELF LIFE:	18 months from the production date
STORAGE:	Temperature: Up to 30°C Relative Humidity: up to 70%



STRONG EUROPE