

SCHWEGO[®] eco fount CS

Fountain additive for coldset printing

Function: **SCHWEGO[®] eco fount CS** is a fountain additive which was especially developed for the requirements of coldset printing.

It can be used with all damping units and is excellently suitable for conventional newspaper production.

SCHWEGO[®] eco fount CS-S for water hardness up to 12° KH
SCHWEGO[®] eco fount CS-M for water hardness from 10° - 18° KH
SCHWEGO[®] eco fount CS-H for water hardness > 16° KH

Properties:

- Excellent anti-linting behaviour (reduces lint build-up)
- Develops a stable ink-water-emulsion even with process and special colours
- Suitable for CtP-plates
- Fast running free behaviour
- Checked and released according to default settings of the machine builders
- Complexing of the hardness formers prevents any deposits on the ink and damping rollers

certified by



Quantity to add: **SCHWEGO[®] eco fount CS** is added to the water with a ratio of 2-4 %.

Packaging: 10 kg / 20 kg canister / 200 kg drum / 600 kg / 1000 kg container

The above information is based on our current knowledge and experience. No binding assurance in respect of certain properties or suitability for certain applications must be read into our information. Patent rights and other proprietary rights must be observed if necessary. Further safety instructions please learn from our material safety data sheet. 01/2017