

## SCHWEGO<sup>®</sup> soft 1000 W / N

### Multifunctional fountain additive for sheetfed offset printing

**Function:** **SCHWEGO<sup>®</sup> soft 1000 W / N** is a universally applicable fountain water additive for sheetfed offset printing. **SCHWEGO<sup>®</sup> soft 1000 W / N** is also very suitable for hybrid technology and for printing with UV-inks.

It offers constant conditions in the printing process by its wide range of applications, even with demanding subjects and problematic substrates.

**SCHWEGO<sup>®</sup> soft 1000 W** for water hardness up to 10° KH  
**SCHWEGO<sup>®</sup> soft 1000 N** for water hardness from 8° to 14° KH

### Properties:

- Excellent anti-linting behaviour (reduces lint build-up)
- Stable ink- water emulsion, especially with process inks and special colours
- Optimized complexing of the hardness formers prevents deposits on the ink and damping rollers
- Stable adjustment of the pH-value
- Fast free running behaviour
- Suitable for CtP-plates
- Checked and released according to the default settings of the leading machine builders

**Quantity to add:** **SCHWEGO<sup>®</sup> soft 1000 W / N** is added to the water with a share of about 2-4%.

**Tip:** Subject to appropriate storage, the described properties of **SCHWEGO<sup>®</sup> soft 1000 W / N** remain stable for at least 12 months.

**Packaging:** 10 kg / 20 kg canister / 200 kg drum / 600 kg / 1000 kg container

The above information is based on our current knowledge and experience. No binding assurance in respect of certain properties or suitability for certain applications must be read into our information. Patent rights and other proprietary rights must be observed if necessary. Further safety instructions please learn from our material safety data sheet. 04/2016