

## SCHWEGO® soft 2000 T

### Fountain additive for coldset printing

**Function:** The **SCHWEGO® soft 2000 T** is a fountain additive especially tailored to the requirements of coldset printing.

It can be used on all printing presses and with all damping units. As a result of reduction of paper waste and lower ink/water supply interesting saving potentials arise.

<b>SCHWEGO® soft 2000 RT</b>	for water hardness of 0° to 4° KH
<b>SCHWEGO® soft 2000 WT</b>	for water hardness up to 10° KH
<b>SCHWEGO® soft 2000 NT</b>	for water hardness of 8° to 14° KH
<b>SCHWEGO® soft 2000 BT</b>	for water hardness of 12° to 18° KH

### Properties:

- Fast running free behaviour
- Reduction of waste paper
- Reduced ink/water supply
- Excellent anti-linting behaviour (reduces lint build-up)
- Stable adjustment of the pH-value
- Checked and released according to default settings of the machine builders
- Complexing of the hardness formers prevents any deposits on the ink and damping rollers

certified by



**Quantity to add:** **SCHWEGO® soft 2000 T** is added to the water with a ratio of 2-3%.

**Tip:** Subject to appropriate storage, the described properties of **SCHWEGO® soft 2000 T** remain stable for at least 12 months.

**Packaging:** 10 kg / 20 kg canister / 200 kg drum / 600 kg / 1000 kg container

The above information is based on our current knowledge and experience. No binding assurance in respect of certain properties or suitability for certain applications must be read into our information. Patent rights and other proprietary rights must be observed if necessary. Further safety instructions please learn from our material safety data sheet. 01/2017