


## SCHWEGO® soft 3000 A

### Fountain additive for heatset printing

**Function:** **SCHWEGO® soft 3000 A** was developed for the comprehensive requirements and possibilities of heatset printing. According to the respective machine configuration and the technical conditions **SCHWEGO® soft 3000 A** will also allow printing without any isopropanol (IPA).

**SCHWEGO® soft 3000 AW** for water hardness values of up to 10° KH  
**SCHWEGO® soft 3000 AN** for water hardness values from 8° up to 14° KH  
**SCHWEGO® soft 3000 AB** for water hardness values from 12° up to 18° KH

### Characteristics:

- Defined setting of the surface and interfacial tension
  - Special wetting agents ensure a reduction of damping and inking
  - Outstanding anti-linting behaviour (reduced lint build-up)
  - Stable setting of pH-values
  - Fast free-running behaviour
- certified by
- 
- Checked and released in accordance with the specifications of the machine builders

**Addition amount:** About 2-4% of **SCHWEGO® soft 3000 A** is added to the water.

**Note:** Detailed information for printing without IPA is available in our **flyer „Printing without alcohol“**.

Storage not under 5 °C

The described characteristics of **SCHWEGO® soft 3000 A** will remain constant for at least 12 months when stored adequately.

**Packaging:** 10 kg / 20 kg canister / 200 kg drum / 600 kg / 1000 kg container

The above information is based on our current knowledge and experience. No binding assurance in respect of certain properties or suitability for certain applications must be read into our information. Patent rights and other proprietary rights must be observed if necessary.  
Further safety instructions please learn from our material safety data sheet. 01/2017